


Wasserabfluss DN100 in der
Vertiefung empfohlen
Water outlet DN 100 in the pit
recommended



Betonqualität
quality of concrete
min.C20/25
normal bewehrt
normal armouring

bausseitiger Winkelrahmen
angle frame by customer


DETTAGLIO "X"

Bauseits am Bedienpult bereitstellen:
Netzanschluss: 3PH+PE, 400V, 50Hz
Motorleistung: 2,6 kW
Absicherung: 10 Ampere träge
Kabellänge: ca. 2m, 4 x 4mm²
Druckluft R3/8" oder Schlauch DN10, 6-8 bar

Prepared by customer at the main operating power supply: 3PH+PE, 400V, 50Hz
Motor power 2,6 kW
fuse: 10 Ampere, time lag
cable diameter: 4 x 4mm²
cable length: approx. 2m
optional: R3/8" or hose DN10, 6-8bar

Wir weisen in unseren Plänen auf die Mindestanforderung des Fundamentes hin, jedoch der Zustand der örtlichen Gegebenheiten (z.B. Untergrund, Ausführung etc.) obliegt nicht unserer Verantwortung. Die Ausbildung der Einbausituation muss vom planenden Architekten bzw. Statiker im speziellen Fall individuell spezifiziert werden.

We point out the minimum requirement of the foundation in our plans. The condition of the local realities for example: the ground under the foundation) does not lie in our responsibility. The execution of the installation situation must be individually specified by the planning architect or by the engineer engaged in statically calculations in the special case.



- * empfohlene Fundamentbreite
recommended foundation width
- ** Aufstellmaß der Hebebühne
Position of the lift

Alle Maße in Millimeter
all dimensions in millimeter

Maß- und Konstruktionsänderungen vorbehalten!
subject to alterations!

					THIRD ANGLE PROJECTION 	S42LT46CAT-I
				UNLESS OTHERWISE NOTED: ANGULAR DIMENSIONS: +/- 1 OTHER DIMENSIONS: +/- 0.8mm (< 305mm) +/-1.6mm (> or= 305mm)	DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: 0.8mm MIN. CORNER BREAK REMOVE ALL BURRS	
				NOTES: Tragfigkeit/capacity: 4200 kg		
				The design and detail illustrated in this drawing is the property of Vehicle Service Group. It is being loaned with the expressed condition that it will not be duplicated or used except by permission and is subject to return upon request.	DRAWN M.D.	DATE 08.02.2021
					APPROVED	SHEET DRAWING NUMBER S42LT46CAT-I (059208780).dft
REV	CO NUM	DATE	BY			